


2000 Series Specifications



Hypoid Saw on Spinning Insert




Steel Sleeved Material Rollers



Sealed Steel Roller Bearings



Measuring System



Dual Rip Pointers



Benefits:

- Cut Accuracy of 1/64"
- Frame Never Goes Out of Square
- Smooth Repetitive Carriage Movement
- Ten Second Tool Swap
- Mobility with Folding Stand and Wheels
- Outstanding Dust Evacuation System
- Minimal Set Up Time
- Rip Cut in Either Direction
- Utilize Stop Block on Left or Right
- Saw Cover Blade Window with Light

Standard Equipment:

- Nickel Chrome Plated Guide Tubes
- Accu-Square Alignment System
- Accu-Glide Sealed Bearing System
- Accu-Fence Material Roller System
- Quick Release Carriage with 2 Locks
- Two Spool Retraction Mechanism
- Powder Coated Steel Frame
- Cord Holder
- Center Material Support

Package Includes:

- Makita 5377NB Hypoid Saw on Spinning Saw Insert Plate
- Standard 7.25" Saw Blade
- Dual Rip Gauges for Left or Right Rip Cuts
- Stop Block with Bar for Cutting Strips
- Dust Hose and Dust Containment Brush
- Folding Stand and Transport Wheels
- Horizontal Measuring Tapes
- Vertical Measuring Tape
- Side Stand Legs
- Steel Sleeved Material Rollers

Optional Accessories:

- Floating Router Insert Plate
- OLFA®Pivoting Knife Insert Plate
- Spring Hold Down
- ACM Rolling Shear Insert Plate
- Sheet Clamp
- Full Builder's Extensions
- Coiled Extension Cord
- Full Mid-Fence
- Frame Dust Collection
- Laser Guide
- Flip Stop System

2000 Series Product Specifications	Full Size	Full Size	Full Size
Model Number	2052	2064	2076
Material Rollers - Steel Sleeved	18	18	18
Maximum Cross Cut	52"	64"	76"
Maximum Rip Cut	Unlimited	Unlimited	Unlimited
Maximum Cut Thickness	1-3/4"	1-3/4"	1-3/4"
Saw Blade Diameter	7-1/4"	7-1/4"	7-1/4"
Arbor Diameter	5/8"	5/8"	5/8"
Saw Motor, Makita 5377NB	15 amp-120 v	15 amp-120 v	15 amp-120 v
Frame Height (set up)	78"	90"	102"
Frame Width (set up)	122"	122"	122"
Frame Depth-Stand closed with Saw	15"	15"	15"
Frame Depth with Stand open	40"	40"	40"
Shipping Weight	440#	480#	490#