


Classic Series Specifications




Makita Saw on Spinning Insert



Sealed Steel Roller Bearings



Measuring Tape



Single Rip Pointers

Benefits:

- Cut Accuracy of 1/64"
- Frame Never Goes Out of Square
- Smooth Repetitive Carriage Movement
- Ten Second Tool Swap
- Minimal Set Up Time
- Rip Cut in Either Direction
- Saw Cover Blade Window with Light

Standard Equipment:

- Nickel Chrome Plated Guide Tubes
- Accu-Square Alignment System
- Accu-Glide Sealed Bearing System
- Accu-Fence Material Roller System (Full Size Only)
- Quick Release Carriage with 2 Locks
- Retraction Mechanism
- Powder Coated Steel Frame
- Cord Holder
- Center Material Support
- Side Stand Legs (Full Size Only)

Optional Accessories:

- Floating Router Insert Plate
- OLFA® Pivoting Knife Insert Plate
- Spring Hold Down
- ACM Rolling Shear Insert Plate
- Sheet Clamp
- Full Builder's Extensions
- Coiled Extension Cord
- Full Mid-Fence
- Frame Dust Collection
- Laser Guide
- Flip Stop System
- Folding Stand
- Transport Wheels
- Dust Hose
- Dust Containment Brush
- Steel Sleeved Material Rollers
- Stop Block with Bar for Cutting Strips
- Wall Mounting Kit



Package Includes:

- Makita 5007F on Spinning Saw Insert Plate
- Standard 7.25" Saw Blade
- Single Rip Gauge
- Dust Containment Hood
- Single Horizontal Measuring Tape
- Vertical Measuring Tape
- Side Stand Legs (Full Size Only)
- Saw Cover and Viewing Port
- Blade Guard
- Trigger Lock



Classic Series					
Product Specifications	Compact	Compact	Full Size	Full Size	Full Size
Model Number	C52C	C64C	FS52C	FS64C	FS76C
Material Rollers - Plastic	10	10	18	18	18
Maximum Cross Cut	52"	64"	52"	64"	76"
Maximum Rip Cut	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
Maximum Cut Thickness	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"
Saw Blade Diameter	7-1/4"	7-1/4"	7-1/4"	7-1/4"	7-1/4"
Arbor Diameter	5/8"	5/8"	5/8"	5/8"	5/8"
Saw Motor, Makita 5007F	15 amp-120 v	15 amp-120 v	15 amp-120 v	15 amp-120 v	15 amp-120 v
Frame Height (set up)	78"	90"	78"	90"	102"
Frame Width (set up)	65-1/4"	65-1/4"	122"	122"	122"
Frame Depth-No Stand, measured with Saw	13"	13"	13"	13"	13"
Frame Depth with Stand open	No Stand Included	No Stand Included	No Stand Included	No Stand Included	No Stand Included
Transport Wheels	No Wheels Included	No Wheels Included	No Wheels Included	No Wheels Included	No Wheels Included
Shipping Weight	276#	296#	370#	396#	412#