

# yel-Low Safety Dolly Specifications



## Benefits:

- Dolly Fits within Standard Doorways
- Move in Any Direction
- Move Multiple Objects, Different Sizes and Weights
- Base Model Dolly Can Carry Up to 1000 lbs
- Durable Welded Unibody Steel Construction

## Standard Equipment:

- 12 Gauge Steel Unibody Box
- Six - 56" square 16 Gauge Posts
- Four 4" Polyurethane Over Cast Iron Casters
- Powder Coated Steel Unibody
- 1000 lb Weight Capacity
- E-Track Strap Access Positions (8)
- Low Loading Height, Lower than a Pallet
- Floor Clearance of 5/8"

## Optional Accessories:

- Additional Posts in Various Lengths
- Dock Transition Wheels
- Brakes (set of 2)
- Corner Protectors/Connectors
- Fixed Direction Caster
- Forklift Posts
- Shelf Plate
- Hi/Lo Caster Bracket Kit



yel-Low Safety Dolly Product Specifications	*Optional Accessories
Material Construction	12 Gauge Steel Unibody
Post Position Locations on Top of Dolly Body (Vertical)	18
Post Position Locations on Sides of Dolly Body (Horizontal)	8
Overall Dimensions Without Posts	30"L x 25"W x 5-1/4"H
Overall Dimensions w/ Posts Installed (56" Posts Vertical)	30"L x 25"W x 57"H
Dock Transition Wheel Material / Weight of 4 Assembly*	4" Solid Polypropylene / 4.7 lbs
Maximum Capacity	1000 lbs
Brakes - Weight Capacity (Set of 2) Assembly*	Brakes Rated 600 lbs Each Holding Capacity
Deck Height	5-1/4"
Floor Clearance	5/8"
Casters - Total Number / Dock Transition Caster*	4 / 5
Casters Size - Wheel Material	4" Polyurethane Over Cast Iron
Casters - Type	Swivel
Finish - Color	Powder Coat Yellow
Weight - Without Posts / With (6) 56" Posts	53 lbs / 93 lbs